"Your Direct Source for Plant Maintenance, Reliability, Test & Measurement"
www.reliabilitydirectstore.com
2911 South Shore Blvd. Suite 170, League City, TX USA 77573 Phone: 281-957-5283 Fax: 281-334-4255

Model 376/CC701HT system
Accelerometer/charge amplifier system

Features
- Industrial ruggedness
- Charge output
- Ground isolated
- 260°C operation

Dynamic

Sensitivity, 25°C	100 mV/g, ±10%
Acceleration range	50 g
Amplitude linearity, to 50 g	1%
Frequency response:	
±10%	2 - 10,000 Hz
±3 dB	1 - 15,000 Hz
Resonance frequency	30 kHz
Transverse sensitivity	7% of axial
Temperature response:	
–50°C	–10%
+260°C	+20%

Electrical

Power requirement:	voltage source	18 - 30 VDC
	current regulating diode	2 - 10 mA
Electrical noise, equiv. g:		
Broadband		0.001 g peak
Output impedance		‹100Ω
Bias output voltage		12 VDC
Grounding		case isolated

Enivironmental

Temperature range:	
376	–50 to 260°C
CC701HT	–40 to 100°C
Vibration limit	500 g peak
Shock limit	5000 g peak
Base strain	0.002 g/µstrain

Physical

Sensing element design	PZT ceramic / compression
Weight:	
376	75 grams
CC701HT	40 grams
Case material	316L stainless steel
Mounting	1/4-28 tapped hole
Mating connector	BNC jack
Standard cabling[1]	R1-1-J3-12

Connector pin	Function
Shell	common
Pin	power / signal



Model 376



Model CC701HT

Notes: [1] Other cable lengths are available
Accessories supplied: Calibration data (level 3)

Reliability Direct, Inc.

Visit our e-commerce stores for plant maintenance and reliability:
www.reliabilitydirectstore.com, www.extech-direct.com