

"Your Direct Source for Plant Maintenance, Reliability, Test & Measurement"

www.reliabilitydirectstore.com

2911 South Shore Blvd. Suite 170, League City, TX USA 77573 Phone: 281-957-5283 Fax: 281-334-4255

Flexible True RMS AC Current Clamp

Flexible 24" (610mm) probe for Current to 3000A

Easily wraps around bus bars and cable bundles with attractive large LCD displaying AC Current, AC Voltage, and Frequency measurements

Features:

- AC Voltage to 600V
- Fast Peak capture (30µs)
- Selectable frequency (50/60Hz)
- Max/Min feature
- Simultaneously displays Frequency with Current or Voltage
- Large 4000 count LCD dual display
- · Auto power off with disable feature
- Complete with 24" (61cm) flexible current probe, carrying case, and 2 AA batteries





Specifications	Range	Max Resolution	Basic Accuracy
AC Current	3 to 3000A	0.1A	±1%
AC Voltage	4 to 600V	0.1V	±0.5%
Frequency	45 to 65Hz	0.1Hz	±0.2Hz
Display	Dual 4000 count LCD		
Probe	24" (610mm) long, 0.55" (14mm) diameter		
Meter	5.1 x 3.15 x 1.7" (130mm x 80mm x 43mm)		
Weight	0.95lb (430g)		

Ordering Information:

382400Flexible True RMS 3000A AC Current Clamp 382400-NIST..Flexible True RMS 3000A AC Current Clamp w/NIST





